Nashua APEPRODUCTS PROFESSIONALS CHOICE 3985A

Low VOC General Purpose Spray Adhesive



Spray Pattern:	Lace/Web	
Color:	Water White	
Application Temp:	40 to 110 °F (4 to 43 °C)	
Bonding Time:	10 seconds to several hours*	
Coverage Area:	Varies	
Shelf Life:	1 Year from DOM	
VOC Content:	<55% by weight	
Meets EDA requirements for indirect food packaging when		

Meets FDA requirements for indirect food packaging when used according to 21 CFR 175.105.

Applications

- Bonding carpets
- Securing insulation materials
- Securing labels
- Suitable for permanent or temporary bonds

Bonding fabric, insulation, plastic films, felt, rubber, leather, cork, paper, cardboard, metal, wood

 Excellent for laminating urethane foam to a variety of substrates

	Features	Benefits
•	Rubber Based	 Fast skin, fast grab, low soak-in
		 Good UV, moisture, and oxidation resistance
٠	Low VOC Content	 Meets SCAQMD Rule 1168 and GreenSeal GS-36
		requirements
		Can contribute toward satisfying EQ Credit 4.1
		(Low Emitting Materials) under LEED®

Application Instructions

- Shake well before applying. Spray an even coat from a distance of 6-8 inches.
- For permanent bonds, spray both surfaces. Allow 1-2 minutes for tack to develop. Apply firm pressure.
- For temporary bonds, apply a light, even coat to one surface; allow tack to develop. Apply firm pressure.
- When finished spraying, turn can upside down and spray for 2 seconds to prevent nozzle from clogging.

Caution: Extremely Flammable. Please review all safety instructions on the product package prior to use.

Recommended Storage Conditions: 32-90 °F at 50% RH $\pm 2\%$ Standard Shelf Life (at 25C): 12 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryplastics.com 9/30/15