


# POLYKEN®

# 1027

## Primer/Liquid Adhesive System



|                    |                            |
|--------------------|----------------------------|
| Base:              | Rubber/Resins              |
| Solvent:           | V. M. & P Naptha           |
| Flash Point:       | 40 °F (-4 °C)              |
| Installation Temp: | 50 to 120 °F (10 to 49 °C) |
| Total Solids:      | 30%                        |
| Coverage Area:     | Varies                     |
| Shelf Life:        | 3 Years from DOM           |
| Weight Per Gallon: | 7.1 lb/gal (0.86 kg/L)     |

Caution: Extremely Flammable. Review all safety information printed on the product package.

- Surface preparation for masonry, concrete, OSB, rigid insulation, wood, and metal
- Promotes adhesion and anchorage prior to installation of window, door and roof flashing
- Brush or roller priming applications
- Promotes adhesion and anchorage prior to installation of pipe wrap tapes

### Features

- Rubber Based

### Benefits

- Good UV, moisture, and oxidation resistance
- Dries to a smooth, uniform finish to provide a superior bonding surface
- Easy to apply, no over-spray

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F  
Standard Shelf Life (at 25°C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.