


## 307

## **Utility Grade Duct Tape**



Backing: PE Coated Cloth

Adhesive: Rubber

Liner: N/A

Colors: Silver, Black

**Specifications:** Tested in accordance with UL 723

Standard Sizes: 48mm x 55m, 72mm x 55m

## **Applications**

- Maintenance and general repair
- Joint sealing and pipe wrapping

- Bundling, patching, and mending
- Heavy-duty box sealing

## Features Benefits

PE-Coated Cloth Backing	<ul> <li>Conformable and hand tearable</li> </ul>	
	<ul> <li>Resists twisting and curling</li> </ul>	
Natural Rubber Adhesive	<ul> <li>Bonds well to most surfaces, good all climate performance</li> </ul>	
Low VOC Content	<ul> <li>Can contribute toward satisfying EQ Credit 4.1</li> <li>(Low Emitting Materials) under LEED®</li> </ul>	

**Typical Test Values** 

	Standard UOM	Metric UOM	Test Method
Total Thickness	7.0 mils	0.178 mm	ASTM D-1000
Adhesion to Steel	65 oz/in	7.11 N/cm	PSTC-101
Adhesion to Backing	38 oz/in	4.16 N/cm	PSTC-101
Tensile Strength	21 lb/in	36.78 N/cm	ASTM D-1000
Elongation	19%		ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
VOC Content	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

