




## **Extreme Weather FSK Tape**



Backing: Foil/Scrim/Kraft Paper Laminate

Adhesive: Acrylic

Liner: Unbleached Natural Kraft Paper

Colors: Aluminum

**Specifications:** UL 723 Classified (≤ 72mm)

Meets FAR 25.853(a)

Standard Sizes: 72mm x 46M

## **Applications**

· Vapor barrier seal for insulation facing

 Sealing insulation and repairing in cooler/ refrigeration applications

Features Benefits

Foil/Scrim/Kraft Lamina	ate Backing •	High strength and tear resistant	
	•	UV, moisture, and mold resistant	
<ul> <li>High Performance Acrylic Adhesive</li> </ul>		Low odor and low VOC content	
	•	High tack, aggressive bond to surfaces	
	•	Excellent performance in extreme cold or heat	
<ul> <li>UL 723 Classified</li> </ul>	•	Meets flammability requirements for use in	
		construction and marine applications	
<ul> <li>Low VOC Content</li> </ul>	•	Can contribute toward satisfying EQ Credit 4.1	
		(Low Emitting Materials) under LEED®	

**Typical Test Values** 

	Standard UOM	Metric UOM	Test Method
Total Thickness	9.5 mils	0.241 mm	ASTM D-1000
Adhesion to Steel	75 oz/in	8.21 N/cm	ASTM D-1000
Tensile Strength	33 lb/in	57.79 N/cm	ASTM D-1000
Operating Temperature	-35 to 260 °F	-37 to 127 °C	
WVTR	>0.02 Perms		Mocon (100° F, 90% RH)
Minimum Application Temp	-5 °F	-20 °C	
Smoke Developed	0		
Flame Spread	0		
VOC Content	<30 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

