




Insulation Jacketing Tape



Backing: Kraft/Scrim/Foil Laminate

Adhesive: Acrylic

Liner: Polycoated Natural Kraft Paper

Colors: White

Specifications: Tested in accordance with UL 723

Standard Sizes: 72mm x 46M

Applications

 Vapor barrier seal for ASJ-faced duct board, pipe insulation, and thermal jacketing Sealing insulation and repairing in cooler/ refrigeration applications

Features Benefits

•	White Kraft/Scrim/Foil Laminate Backing	High strength and tear resistant	
		Molo	resistant
•	Acrylic Adhesive	Low	odor adhesive
		 Super 	er high tack, aggressive bond to surfaces
•	Low VOC Content	• Can	contribute toward satisfying EQ Credit 4.1
		(Low	Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	11.0 mils	0.279 mm	ASTM D-1000
Adhesion to Steel	50 oz/in	5.47 N/cm	PSTC-101
Tensile Strength	45 lb/in	78.81 N/cm	ASTM D-1000
Operating Temperature	-35 to 260 °F	-37 to 126 °C	
Smoke Developed	25		
Flame Spread	5		
WVTR	0.02 perms		ASTM E96
Emmissivity	0.03		ASTM E408
VOC Content	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

