POLYKEN®



-

Applications

٠	Taping joints and seams in duct work for A/C,	٠	General purpose industrial and automotive uses.
	heating, and ventilation systems	•	Insulation seaming and patching

Features	Benefits
Aluminum Foil Backing	 Conformable to fit corners and joints
	UV and moisture resistant
	 Mold and mildew resistant
Synthetic Rubber Adhesive	 Non-solvent for less odor and low VOC content
	 Extreme high tack, aggressive bond to surfaces
	 Good all-weather performance
UL 723 Classified	 Meets flammability requirements for use in
	construction and marine applications
Low VOC Content	 Can contribute toward satisfying EQ Credit 4.1
	(Low Emitting Materials) under LEED®

Standard UOM	Metric UOM	Test Method
3.2 mils	0.081 mm	ASTM D-1000
1.5 mils	0.038 mm	ASTM D-1000
100 oz/in	10.94 N/cm	PSTC-101
11 lb/in	19.26 N/cm	ASTM D-1000
40 to 200 °F	4 to 93 °C	
0		
10		
<1 g/L		
	3.2 mils 1.5 mils 100 oz/in 11 lb/in 40 to 200 °F 0 10	3.2 mils 0.081 mm 1.5 mils 0.038 mm 100 oz/in 10.94 N/cm 11 lb/in 19.26 N/cm 40 to 200 °F 4 to 93 °C 0 10

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL. INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

