
## POLYKEN®



## Multi-Purpose Foil Tape



Backing:	1.75 mil Aluminum Foil		
Adhesive:	Synthetic Rubber		
Liner:	Polycoated Natural Kraft Paper		
Colors:	Aluminum		
Specifications:		UL 723 Classified	
Standard Sizes:		48mm x 46M, 72mm x 46M	

## Applications

Taping joints and seams in duct work for A/C,
 General purpose industrial and automotive uses
 Insulation seaming and patching

Features	Benefits
Aluminum Foil Backing	<ul> <li>Conformable to fit corners and joints</li> <li>UV and moisture resistant</li> <li>Mold and mildew resistant</li> </ul>
Synthetic Rubber Adhesive	<ul> <li>Non-solvent for low odor and low VOC content</li> <li>Extreme high tack, aggressive bond to surfaces</li> <li>Good all-weather performance</li> </ul>
UL 723 Classified	<ul> <li>Meets flammability requirements for use in construction and marine applications</li> </ul>
Low VOC Content	<ul> <li>Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®</li> </ul>

## **Typical Test Values**

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.7 mils	0.094 mm	ASTM D-1000
Foil Thickness	1.75 mils	0.044 mm	ASTM D-1000
Adhesion to Steel	100 oz/in	10.94 N/cm	PSTC-101
Tensile Strength	14 lb/in	24.52 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Smoke Developed	10		
Flame Spread	10		
VOC Content	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

