
# **POLYKEN®**



## **Premium Gaffer's Tape**



Backing: Matte-Finish Vinyl Coated Cloth

Adhesive: Rubber

Liner: N/A

Black, White, Gray, Brown, Red, Burgundy, Colors:

Yellow, Dk Green, Beige, Navy, Ral Yellow, Neon

Green, Neon Orange, Neon Yellow, Neon Pink, Neon Blue, Royal Blue, Purple, Teal

Tested in accordance with UL 723 **Specifications:** 

**Standard Sizes:** 48mm x 50m, 72mm x 50m

### **Applications**

- Protect and anchor wiring in the photography Wrapping or bundling wire, metals, and plastics and film industry, convention, and hospitality • Color Coding
- Place marking/spike tape
- Vinyl seat repair

- General repair
- Bookbinding

#### **Features Benefits**

•	Heavy-Duty Vinyl-Coated Cloth Backing	<ul> <li>Matte-finish for less reflectivity and low sheen</li> </ul>	
		<ul> <li>Excellent durability and conformability</li> </ul>	
•	Natural Rubber Adhesive	<ul> <li>High tack for a variety of surfaces</li> </ul>	
		<ul> <li>Clean removal - no residue</li> </ul>	
•	Low VOC Content	<ul> <li>Can contribute toward satisfying EQ Credit 4.1</li> </ul>	
		(Low Emitting Materials) under LEED®	

#### **Typical Test Values**

	Standard UOM	Metric UOM	Test Method
Total Thickness	11.5 mils	0.292 mm	ASTM D-1000
Adhesion to Steel	50 oz/in	5.47 N/cm	PSTC-101
Adhesion to Backing	29 oz/in	3.17 N/cm	PSTC-101
Tensile Strength	42 lb/in	73.55 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Smoke Developed	10		
Flame Spread	30		
VOC Content	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 12 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently

