
## POLYKEN®

## 1° 512 Multi-Purpose Gaffer's Tape



Backing:	Matte	-Finish Vinyl Coated Cloth
Adhesive:	Clear	Synthetic Rubber
Liner:	N/A	
Beige		, White, Gray, Brown, Red, Yellow, Dk Green, e, Navy, Ral Yellow, Neon Green, Neon ge, Neon Yellow, Neon Pink
Specificatio	ons:	N/A
Standard Si	zes:	48mm x 50m, 72mm x 50m

## **Applications**

٠	Protect and anchor wiring in the photography •	Wrapping or bundling wire, metals and plastics
	and film industry, convention, and hospitality •	Color Coding
٠	Bookbinding •	General repair
٠	Vinyl seat repair	

Features	Benefits	
Heavy-duty vinyl coated backing	Matte-finish for less reflectivity and low sheen	
	<ul> <li>Excellent durability and conformability</li> </ul>	
<ul> <li>Synthetic rubber based adhesive</li> </ul>	<ul> <li>Super high tack for a variety of surfaces</li> </ul>	
	<ul> <li>Clean removal - no residue</li> </ul>	
	• Clear	
Low VOC Content	<ul> <li>Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®</li> </ul>	

Typical Test Values								
	Standard UOM	Metric UOM	Test Method					
Total Thickness	12.0 mils	0.305 mm	ASTM D-1000					
Adhesion to Steel	66 oz/in	7.22 N/cm	PSTC-101					
Adhesion to Backing	27 oz/in	2.95 N/cm	PSTC-101					
Tensile Strength	40 lb/in	70.05 N/cm	ASTM D-1000					
Operating Temperature	40 to 200 °F	4 to 93 °C						

. \_

. . . .

Recommended Storage Conditions: 60-80 °F at 40-60% RH Standard Shelf Life (at 25C): 12 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.



## 25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryglobal.com