


Multi-Purpose PE Tape



Backing: Polyethylene Film

Adhesive: Synthetic Rubber

Liner: N/A

Colors: Red, White, Black, Silver, Teal, Blue, Orange,

Clear, Pink*, Green*

Specifications: N/A

Standard Sizes: 48mm x 55m, 72mm x 55m

Applications

- Abatement industry: hang and patch poly sheeting, seal waste disposal bags, etc.
- Labeling and color coding
- Short-term masking for stucco and plaster
- Bundling, wrapping, and repairs
- Temporary surface protection

- Convention industry bundling carpet, securing poly carpet protection, color coding, etc.
- Seam and patch shrink wrap for indoor/outdoor storage of marine, RV, and other equipment
- Film-to-film splicing
- Dissimilar metal tape

Features Benefits

Polyethylene Film Backing	Conformable and flexible		
	 Excellent durability and solvent resistance 		
	 Low elongation for consistant surface bond 		
	 Pinked Edge available for hand tearability 		
 Synthetic Rubber Adhesive 	 High tack for good quick stick 		
	 Excellent shear strength 		
	 Repositionable and clean removal from many surfaces 		
 Low VOC, <u>Contains no heavy metals</u> (such as lead and chromium) 	Environmentally friendly & safe to use.		

Typical Test Values

	Standard UOM	Metric UOM	Test Method	
Total Thickness	7.0 mils	0.178 mm	ASTM D-1000	
Adhesion to Steel	75 oz/in	8.21 N/cm	PSTC-101	
Adhesion to Backing	35 oz/in	3.83 N/cm	PSTC-101	
Tensile Strength	25 lb/in	43.78 N/cm	ASTM D-1000	
Permeance	0.11 US Perms		ASTM F1249	
Application Temperature	30 to 160 °F	-1 to 71 °C		
Operating Temperature	20 to 200 °F	-7 to 93 °C		
Flongation	85%			

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use compiles with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal



^{*} Subject to availability and minimum order