
POLYKEN®

BO9 PE Abatement/Tarp Tape



Backing:	Polyethylene Film	
Adhesive:	Rubber	
Liner:	N/A	
Colors:	Black	x, Yellow
Specifications:		N/A
Standard Sizes:		48mm x 55m, 72mm x 55m

Applications

 Hang, seam, and patch PE sheeting during abatement, remediation, and cleaning Seal polyethylene waste disposal bags 	 Hang, seam, and patch heavy duty tarp materials both indoors and outdoors General purpose abatement applications 				
Features	Benefits				
Polyethylene Film Backing	 Highly conformable and flexible Excellent durability and solvent resistance Clean easy tear 				
Natural rubber based adhesive	 High tack for a secure bond Repositionable and clean removal - no residue Strength of a duct tape without the irregular adhesive surface 				

Typical Test Values

	71			
	Standard UOM	Metric UOM	Test Method	
Total Thickness	7.5 mils	0.191 mm	ASTM D-1000	
Adhesion to Steel	50 oz/in	5.47 N/cm	PSTC-101	
Adhesion to Backing	25 oz/in	2.74 N/cm	PSTC-101	
Tensile Strength	25 lb/in	43.78 N/cm	ASTM D-1000	
Operating Temperature	40 to180 °F	4 to 82 °C		
Elongation	70%			

Recommended Storage Conditions: 60-80 °F at 40-60% RH Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

