

ALF120L

1.2 MIL ALUMINUM FOIL TAPE ON LINER

DESCRIPTION

ALF120L aluminum foil tape features an aggressive Synthetic Rubber based pressure sensitive adhesive on a removable release coated paper liner.

PRODUCT APPLICATIONS

Engineered for seaming and sealing FSK based fiberglass duct board and duct wrap to enhance appearance. Aggressive adhesive provides quick / positive grab to surfaces.

SERVICE TEMPERATURE RANGE

-4°F (-20°C) to +176°F (+80°C)

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing ASTM C-1136	1.2 mil (30μ) Aluminum Foil
Adhesive	Synthetic Rubber
Tensile Strength (lbs./in) PSTC-131	10.3 (45 N/25mm)
Elongation (% at break) PSTC-131	3
Adhesion to Steel (oz/in) PSTC-101	91 (99.5 N/25mm)
Total Thickness w/o liner (mil) PSTC-133	2.8 (0.07 mm)



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 03/20

