

AC45

12 MIL MEDIUM GRADE DUCT TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

Polyethylene (PE) coated cloth film with an aggressive pressure sensitive natural rubber adhesive that provides a wide range of temperature resistance. Conformable. Hangs and tears straight. Specifically designed to meet the needs of the general contractor.

PRODUCT APPLICATION

General contractor, HVAC (heating, ventilation and air conditioning) applications, asbestos/lead/fiberglass abatement.

GOVERNMENT COMPLIANCE

Meets HUD, BOCA and L.A. County codes. Tested in accordance with UL-723.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

| | |
|--|----------------------------------|
| Backing | PE Film |
| Adhesive | Natural Rubber/Resin |
| Reinforcement | PET Cloth |
| Tensile Strength (lbs./in of width) PSTC-131 | 24 (105 N/25mm) |
| Elongation (% at break) | 19 |
| Adhesion to Steel (oz/in of width) PSTC-101 | 50 (13.7 N/25mm) |
| Total Thickness (mils) PSTC-133 | 12.0 (0.305mm) |
| Colors | Silver, Black, Red |
| Temperature Resistance | +32°F ~ +200°F (+0°C ~ +93°C) |



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 03/20

