PF14

SPECIALTY IDENTIFICATION PAPER FLATBACK TAPE

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

A medium tensile strength, pressuresensitive, kraft flatback, paper packaging and identification tape. Specially formulated adhesive provides for easier unwind while exhibiting an excellent balance of face to face adhesion and quick stick characteristics. Printable with standard flexographic ink.

PRODUCT APPLICATIONS

Designed for light-weight packaging, bag locking, decorative edging, marking and color coding.

GOVERNMENT CONFORMANCE

A-A-883, Type II ASTM D6123, D6123M, Type II General Motors 9885278

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

BackingKraft FlatbackAdhesiveSynthetic RubberAdhesion to Steel (oz/in of width)50 (13.7 N/25mm)PSTC-101PSTC-101

Quick Stick (oz/in of width)

To Kraft 8 (2.2 N/25mm)
To Steel 23 (6.3 N/25mm)

Tensile Strength (lbs/in of width) 31 (136 N/25mm)

PSTC-131

Elongation (% at break) 3

PSTC-131

Total Thickness (mils) 6.3 (0.16mm)

PSTC-133

Colors White, Yellow, Blue,

Red, Orange, Pink, Light Green



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/13



