

# PS3

## NATURAL PREMIUM PAPER FLATBACK TAPE

# INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### DESCRIPTION

High performance, water resistant, kraft flatback, pressure sensitive tape. Features easy release from roll, good quick-stick, excellent bonding to cartons and good edge tear resistance. Performs well as a low temperature splicing tape. Product is not repulpable.

### PRODUCT APPLICATION

Designed for heavy duty packaging closure and tabbing.

### GOVERNMENT COMPLIANCE

PPP-T-76C-Type V  
A-A-1830, Type I, Class 1  
A-A-884, Type I, Class 1

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	Kraft Flatback
<b>Adhesive</b>	Natural Rubber / Resin
<b>Tensile Strength</b> (lbs/in of width) MD	51 (223 N/25mm)
ASTM D3759 CD	32 (140 N/25mm)
<b>Elongation</b> (% at break) ASTM D3759	3.3
<b>Adhesion to Steel</b> (oz/inch) ASTM D3330	78 (21 N/25 mm)
<b>Total Thickness</b> (mil) ASTM D3652	7.9 (0.20 mm)
<b>Operating Temperature Range</b>	+32°F ~ +250°F (0°C ~ +121°C)
<b>Color</b>	Beige



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 4/17

