

PS8

HIGH TEMP PREMIUM PAPER FLATBACK TAPE

DESCRIPTION

Strong, natural colored kraft flatback paper with temperature resistant acrylic adhesive. Product is not repulpable. Temperature resistant.

PRODUCT APPLICATION

For splicing of light floor covering and similar materials during manufacturing. Also for leasing / beaming synthetic fibers.



intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 03/17

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Kraft Flatback
Adhesive	Solvent Acrylic
Tensile Strength (lbs/in of width) MD	54 (236 N/25mm)
ASTM D-3759 CD	32 (140 N/25mm)
Elongation (% at break)	4
ASTM D-3759	
Adhesion to Steel (oz/in width)	54 (15 N/25 mm)
ASTM D-3330	
Total Thickness (mil)	9.1 (0.23 mm)
ASTM D-3652	
Operating Temperature Range	+40°F ~ +350°F (4°C ~ +176°C)
Color	Beige

