PT8 8 DAY UV-RESISTANT SPECIALTY PAPER MASKING TAPE

DESCRIPTION

Light green crepe paper masking tape with a specially formulated pressure-sensitive, synthetic rubber adhesive. Designed for direct exposure to sunlight up to eight days. Conformable, consistent, easy unwind. Resistant to humidity and paint bleed through. Secure adhesion with easy, clean removal from most surfaces. (Caution: green color is a dye added to paper)

PRODUCT APPLICATION

Wherever masking will be exposed to weather / out-of-doors conditions. Interior masking of windows (where adhesive could be directly exposed to sunlight). Compatible for use on lacquer or polyurethane-coated surfaces, unfinished wood, wallpaper, or new, unpainted, or freshly painted wallboard.



intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/11

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

PHYSICAL PROPERTIES

- -

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Crepe Paper
Adhesive	Synthetic Rubber
Adhesion to Steel (oz/in of width) PSTC-101	22 (6 N/25mm)
Tensile Strength (Ibs/in of width) PSTC-131	18 (79 N/25mm)
Elongation (% at break) PSTC-131	11
Total Thickness (mils) PSTC-133	5.9 (0.15mm)
Quick Stick (oz/in of width) To Steel PSTC-5	8.5 (2.3 N/25mm)
Color	Light Green

