

MERCO TAPE – TECHNICAL DATA SHEET

Merco Carton Sealing Tapes

M1519 General Purpose and M1515 Economy


Merco M1519 General Purpose Carton Sealing Tape is a medium weight shipping grade made of a biaxially oriented polypropylene (BOPP) film coated with a high-grade aggressive emulsion based acrylic adhesive. M1519 available in industry standard hand-length rolls of 48mm x 55yd and 48mm x 110yd, as well as 72mm x 110yd. Stocked in Clear and Tan colors.

Merco M1519 General Purpose Carton Sealing Tape is designed for general box sealing and other packaging applications in shipping, warehouse, retail and on the factory floor. M1519 is also ideal for bundling, wrapping and reinforcing the wrapping of pallets.

Merco M1515 Economy Purpose Carton Sealing Tape

is a lighter weight shipping grade, biaxially oriented polypropylene (BOPP) carton sealing tape coated with a high-grade aggressive emulsion based acrylic adhesive. M1515 available only in hand-length rolls of 48mm x 55yd and 48mm x 110yd. Stocked in Clear.

Merco M1515 General Purpose Carton Sealing Tape is designed for small to medium weight boxes exposed to nominal shipping hazards and stresses. Its used extensively by movers, homeowners, and those with lighter weight requirements in shipping, warehouse or on the factory floor. Excellent applied by hand or dispenser. Good stuff and priced at exceptional price-points. Still, the Queen would not be happy if you used this for the Crown Jewels. (Don't get her angry: try our M1400 Premium Grade.)



	Tensile lbs./in width	Adhesion to Steel oz/in width	Thickness in mils	Elongation %	Application Temperature	Operating Temperature
M1519	20	20	1.7	180	32°F ~ +150°F (0°C ~ +50°C)	30°F ~ +200°F (-35°C ~ 90°C)
M1515	17	20	1.5	150	32°F ~ +150°F (0°C ~ +50°C)	30°F ~ +200°F (-35°C ~ 90°C)

Merco Tape

Info@MercoTape.com

(845) 357-3699

Buy@MercoTape.com

www.MercoTape.com

www.ElectricalTape.com

www.MaskingTape.com