

MERCO TAPE – TECHNICAL DATA SHEET

Merco M806 series Safety Stripe Tapes



Merco M806 PVC Safety Stripe Tapes are a superior quality, self-wound PVC (Poly Vinyl Chloride) Striped Tape intended to meet OSHA, and common sense, marking requirements. Its synthetic rubber adhesive system ensures good stick to your surface and an excellent quality PVC carrier handles lots of tough wear and abusive traffic. It provides excellent elongation for hand application and conformity around difficult areas in warehouses, manufacturing facilities, offices, laboratories and more. Recently (2020-2021) **Merco M806 PVC Safety Stripe Tapes** have been used for social distancing markers.

Merco M806 PVC Safety Stripe Tapes are ideal for hazard awareness, informational markings and for OSHA mandated warnings. OSHA requires Yellow and Black for 'hard' surfaces. Walls, doors, shelves and racking, obstructions, steps, low entry ways and general hazard areas. (Hit one and you will know where else it should go.) Red and White are standard colors required to signifying placement of fire protection equipment, first aid and similar.

See Merco M804 Colored Vinyl Tape for similar marking utility in solid colors.

Yellow and **Black** is cut on the floor in 1" x 18yd, 2" x 18yd, 2" x 36yd, 3" x 18yd

Red and **White** is cut on the floor in 2" x 18yd.

Other widths, lengths and colors available on application. Pls. inquire.

Thickness: 6 mil Tensile Strength: 14 lbs./inch Elongation: 150% Adhesion to Steel: 18 oz./inch
Working Temp: up to 140F (60C)

Merco Tape

Info@MercoTape.com

(845) 357-3699

Buy@MercoTape.com

www.MercoTape.com www.ElectricalTape.com www.MaskingTape.com

rev. November 1 2020