

MERCO TAPE – TECHNICAL DATA SHEET

Merco M807 series Cloth FRICTION TAPE



Merco M807 series Friction Tape is made from a quality cotton cloth, fully impregnated with a non-corrosive rubber compound adhesive. M807 has superior strength and resistance to abrasion & moisture and offers maximum elasticity for a cloth tape. M807 will not fray or ravel. Its cloth backing makes M807 easily hand tearable and very conformable.

Merco M807 series Friction Tape's primary application is for insulation, protection and binding of industrial grade harness installations in situations requiring protection from physical damage caused by friction and rubbing when applied to joints of electrical wires and cables. It is also used as electrical tape in period restoration work.

Each roll of **Merco M807 series Friction Tape's** is wound on a 1-1/2 inch core and packaged in a neutral, non-branded donut overwrap. 2" size is plain shrink wrap. Both are 60 feet in length

Thickness: 15 mils
Adhesion: 15-oz/inch width
Tensile: 50lbs. /inch width
Elongation: 8%
Temperature Range: n/a
Dielectric strength: 1200 volts

Similar in specifications and performance to 3M and Temflex 1755, and Plymouth 1002, 1004, 1006

Merco Tape

Info@MercoTape.com

(845) 357-3699

Buy@MercoTape.com

www.MercoTape.com

www.ElectricalTape.com

www.MaskingTape.com