

# MERCO TAPE – TECHNICAL DATA SHEET

## Merco M920 series Aluminum Foil Tapes



Merco M920 Aluminum Foil Tape is a 50 micron (2-mil) nominal dead soft aluminum foil with an aggressive cold weather solvent acrylic adhesive and protected by easy release liner.

Superior performance, professional grade 2-mil foil tape. Ideally suited for sealing joints / seams against moisture and vapor on foil jacketing insulation. Excellent for refrigeration industry. Suitable for many other permanent sealing, holding, splicing or masking applications.

Packaged with a bi-lingual point of purchase label, with specs and UPC.

M920-48 48mm x 46M packed 24 per case

M920-72 72mm x 46M packed 16 per case

**Thickness: 2 mil Tensile Strength: 70 lbs./inch Elongation: 3.5% Adhesion to Steel: 96 oz./inch**

Working Temp: -40F to 248F (-40C to 120C)

Application Temp: 23F to 104F (-5C to 40C)

## Merco Tape

[Info@MercoTape.com](mailto:Info@MercoTape.com)

(845) 357-3699

[Buy@MercoTape.com](mailto:Buy@MercoTape.com)

[www.MercoTape.com](http://www.MercoTape.com)

[www.ElectricalTape.com](http://www.ElectricalTape.com)

[www.MaskingTape.com](http://www.MaskingTape.com)

rev. November 1 2020