

CF 740

Shurtape®
TRUE TO YOUR WORK™

HIGH PERFORMANCE GRADE, HIGH TEMPERATURE MASKING TAPE

TYPICAL APPLICATIONS

- For high-temperature, demanding industrial paint masking applications in the transportation (auto, coaches, buses and marine) and metal fabrication industries
- Also used for EPDM rubber insulation protection
- Recommended for indoor use only

PRODUCT FEATURES

- Medium-high adhesion
- Easy to unwind
- Excellent quick stick and adhesion to metal, rubber, plastic and fiberglass
- Clean, flat edges for sharper paint lines
- Residue-free removal with no paint flake after baking and extended application periods
- Temperature-resistant up to 350 F

CONSTRUCTION

Overall Grade/Function: High Performance
Backing: Fine structured crepe (FSC)
Adhesive: Rubber-based

STANDARD WIDTH(S)

18 mm 24 mm 36 mm 48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I

COLOR(S)



PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	25 lbs/in width	43.8 N/10 mm
Adhesion to Stainless Steel	39 oz/in width	4.27 N/10 mm
Thickness	6.3 mils	0.16 mm
Elongation	11%	11%
Service Temperature Range	45 F to 350 F	7 C to 176 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

