

## PACKAGING PREMIUM GRADE BLEACHED FLATBACK PAPER TAPE

### TYPICAL APPLICATIONS

- For splicing various substrates
- Also used for heavy duty hand and machine carton sealing applications
- Also used for general purpose applications where a thick, flatback paper tape is required
- Meets or exceeds requirements for motor freight, railway, air express, air freight, postal shipments and government packaging when used as a carton sealing tape

### PRODUCT FEATURES

- Very high adhesion
- Excellent quick stick
- Resistant to abrasion, water, solvents and oil

### CONSTRUCTION

Overall Grade/Function: Packaging Premium  
 Backing: Heavy duty bleached flatback paper  
 Adhesive: Rubber-based

### STANDARD WIDTH(S)

48 mm    72 mm

### STANDARD LENGTH(S)

55 m    110 m

Contact your Shurtape sales representative for other available sizes

### APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type II; ASTM D 5486M-12, Type V

### COLOR(S)



### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	55 lbs/in width	96.3 N/10 mm
Adhesion to Stainless Steel	63 oz/in width	6.90 N/10 mm
Thickness	7.5 mils	0.19 mm
Elongation	3%	3%
Service Temperature Range	50 F to 180 F	10 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

